

SPECIFICATIONS

CIO-DAC02/16

Dual 16-bit Analog Outputs



**MEASUREMENT
COMPUTING™**

Revision 5, October, 2000

© Copyright 2000, MEASUREMENT COMPUTING CORPORATION

POWER CONSUMPTION

+ 5V Supply	400 mA Typical / 675 mA Max.
+ 12V Supply	None
- 12V Supply	None

ANALOG OUTPUTS

Outputs	2
Resolution	16 Bits (1 part in 65536)
Type	AD660BN
Output Ranges:	$\pm 10V$, $\pm 5V$, $\pm 2.5V$, 0 to 10V, 0 to 5V, 0 to 2.5V
Latches	Double-Buffered
Update	Individual or Simultaneous (Jumper Select)
Power Up/Reset	DAC Output forced to 0 Volts
Offset Error	Adjustable to 0
Gain Error	Adjustable to 0
Differential Linearity	± 1 LSB Max.
Integral Non linearity	± 1 LSB Max.
Monotonicity	Guaranteed to 15 bits over temp range
Gain Drift	± 15 ppm/C Max
Bipolar Offset Drift	± 5 ppm/C Max
Unipolar Offset Drift	± 3 ppm/C Max
Slew Rate	2.8V/ μ s Typical
Settling Time:	
20 Volt Step to 0.0008%	12 μ s typical, 19 μ s max
10 Volt Step to 0.0008%	6 μ s typical, 9 μ s max
Current Drive	± 5 mA Min
Output Resistance (Op27)	0.1 Ohm Max
Output Short Circuit Duration	40 mA Min Continuous

ENVIRONMENTAL

Operating Temperature	0 to 70 Deg. C
Storage Temperature	-40 to +100 Deg. C
Humidity	0 to 90% Non-condensing

Measurement Computing Corporation
10 Commerce Way
Suite 1008
Norton, Massachusetts 02766
(508) 946-5100
Fax: (508) 946-9500
E-mail: info@mccdaq.com
www.mccdaq.com