

PCI-DDA08/12

Specifications



**MEASUREMENT
COMPUTING™**

Document Revision 1.0, February, 2010
© Copyright 2010, Measurement Computing Corporation

Specifications

Typical for 25 °C unless otherwise specified.

Specifications in *italic text* are guaranteed by design.

Power consumption

Table 1. Power consumption specifications

| | |
|----------------|--------------------------|
| +5 V operating | 1.6 A typical, 2.6 A max |
| +12 V | 24 mA typical, 48 mA max |
| -12 V | 16 mA typical, 25 mA max |

Analog output

Table 2. Analog output specifications

| | |
|---|---|
| D/A converter type | AD7837B |
| Resolution | 12-bits |
| Number of channels | 8 |
| Output ranges | ± 10 V, ± 5 V, ± 2.5 V, 0 to 10 V, 0 to 5 V, 0 to 2.5 V. Each channel independently programmable. |
| Data transfer | Programmed I/O |
| Offset error (calibrated) | $\pm(300 \mu\text{V} + \frac{1}{4} \text{LSB})$ |
| Gain error (calibrated) | $\pm(300 \mu\text{V} + \frac{1}{4} \text{LSB})$ |
| Differential nonlinearity | ± 1 LSB max |
| Integral nonlinearity | ± 1 LSB max |
| Monotonicity | 12-bits |
| D/A gain drift | ± 2 ppm/°C |
| D/A offset drift | $\pm 5 \mu\text{V}/^\circ\text{C}$ |
| Throughput | PC dependent |
| Settling time (20V step to $\pm \frac{1}{2}$ LSB) | 6 μs typ, 10 μs max |
| Slew rate | 5 V/ μs |
| Current drive | ± 5 mA |
| Output short-circuit duration | 25 mA indefinite |
| Output coupling | DC |
| Output impedance | 0.1 Ohms max |
| Miscellaneous | <ul style="list-style-type: none">▪ Double buffered output latches▪ Update DACs individually or simultaneously (software selectable)▪ Power up and reset, all DAC's cleared to 0 volts, ± 210 mV |

Digital input / output

Table 3. Digital I/O specifications

| | |
|-------------------------------|---|
| Digital type (main connector) | 82C55 mode 0 emulation |
| | Output: 74S244 |
| | Input: 74LS373 |
| Configuration | 4 banks of 8, 4 banks of 4, programmable by bank as input or output |
| Number of channels | 48 I/O |
| Output high | 2.4 volts min @ -15 mA |
| Output low | 0.5 volts max @ 64 mA |
| Input high | 2.0 volts min, 7 volts absolute max |
| Input low | 0.8 volts max, -0.5 volts absolute min |
| Power-up / reset state | Input mode (high impedance) |

Environmental

Table 4. Environmental specifications

| | |
|-----------------------------|-------------------------|
| Operating temperature range | 0 to 70 °C |
| Storage temperature range | -40 to 100 °C |
| Humidity | 0 to 90% non-condensing |

Main connector and pin out

Table 5. Board connectors, cables, accessory equipment

| | |
|---|---|
| Connector type | 100-pin, high density connector |
| Compatible cables | C100FF-x unshielded ribbon cable (x = length in feet) |
| Compatible accessory products with the C100FF-x cable | CIO-TERM100 CIO-MINI50 (two required) |

Table 6. I/O connector pin out

| Pin | Signal Name | Pin | Signal Name |
|-----|----------------|-----|-------------------|
| 1 | Vout 0 | 51 | SECONDPORTA Bit 7 |
| 2 | Analog Ground | 52 | SECONDPORTA Bit 6 |
| 3 | Vout 1 | 53 | SECONDPORTA Bit 5 |
| 4 | Analog Ground | 54 | SECONDPORTA Bit 4 |
| 5 | Vout 2 | 55 | SECONDPORTA Bit 3 |
| 6 | Analog Ground | 56 | SECONDPORTA Bit 2 |
| 7 | Vout 3 | 57 | SECONDPORTA Bit 1 |
| 8 | Analog Ground | 58 | SECONDPORTA Bit 0 |
| 9 | Vout 4 | 59 | SECONDPORTB Bit 7 |
| 10 | Analog Ground | 60 | SECONDPORTB Bit 6 |
| 11 | Vout 5 | 61 | SECONDPORTB Bit 5 |
| 12 | Analog Ground | 62 | SECONDPORTB Bit 4 |
| 13 | Vout 6 | 63 | SECONDPORTB Bit 3 |
| 14 | Analog Ground | 64 | SECONDPORTB Bit 2 |
| 15 | Vout 7 | 65 | SECONDPORTB Bit 1 |
| 16 | Analog Ground | 66 | SECONDPORTB Bit 0 |
| 17 | NC | 67 | SECONDPORTC Bit 7 |
| 18 | NC | 68 | SECONDPORTC Bit 6 |
| 19 | NC | 69 | SECONDPORTC Bit 5 |
| 20 | NC | 70 | SECONDPORTC Bit 4 |
| 21 | NC | 71 | SECONDPORTC Bit 3 |
| 22 | NC | 72 | SECONDPORTC Bit 2 |
| 23 | NC | 73 | SECONDPORTC Bit 1 |
| 24 | NC | 74 | SECONDPORTC Bit 0 |
| 25 | NC | 75 | FIRSTPORTA Bit 7 |
| 26 | NC | 76 | FIRSTPORTA Bit 6 |
| 27 | NC | 77 | FIRSTPORTA Bit 5 |
| 28 | NC | 78 | FIRSTPORTA Bit 4 |
| 29 | NC | 79 | FIRSTPORTA Bit 3 |
| 30 | NC | 80 | FIRSTPORTA Bit 2 |
| 31 | NC | 81 | FIRSTPORTA Bit 1 |
| 32 | NC | 82 | FIRSTPORTA Bit 0 |
| 33 | NC | 83 | FIRSTPORTB Bit 7 |
| 34 | NC | 84 | FIRSTPORTB Bit 6 |
| 35 | NC | 85 | FIRSTPORTB Bit 5 |
| 36 | NC | 86 | FIRSTPORTB Bit 4 |
| 37 | NC | 87 | FIRSTPORTB Bit 3 |
| 38 | NC | 88 | FIRSTPORTB Bit 2 |
| 39 | NC | 89 | FIRSTPORTB Bit 1 |
| 40 | NC | 90 | FIRSTPORTB Bit 0 |
| 41 | NC | 91 | FIRSTPORTC Bit 7 |
| 42 | NC | 92 | FIRSTPORTC Bit 6 |
| 43 | NC | 93 | FIRSTPORTC Bit 5 |
| 44 | NC | 94 | FIRSTPORTC Bit 4 |
| 45 | NC | 95 | FIRSTPORTC Bit 3 |
| 46 | NC | 96 | FIRSTPORTC Bit 2 |
| 47 | NC | 97 | FIRSTPORTC Bit 1 |
| 48 | NC | 98 | FIRSTPORTC Bit 0 |
| 49 | NC | 99 | +5V |
| 50 | Digital Ground | 100 | Digital Ground |

Measurement Computing Corporation
10 Commerce Way
Suite 1008
Norton, Massachusetts 02766
(508) 946-5100
Fax: (508) 946-9500
E-mail: info@mccdaq.com
www.mccdaq.com